

## GRP Kiosk



The GRP Telephone Kiosk is designed for extremely noisy internal or external installations and is suitable for harsh environments, providing a weatherproof and quieter telephone area.



### **Manufacturing**

Manufactured in glass reinforced plastic, the outward opening door has a polycarbonate glazed panel, is fitted with an automatic door closer and has a robust handle. A sloped roof prevents collection of moisture and rainwater.

Internally the three sides of the kiosk are pre-lined with 50mm non-combustible, non-hygroscopic acoustic insulation (density 60kg per cubic metre). This is held in place by galvanised perforated panels. An acoustic slab is placed inside the roof cavity for further insulation.

### **Mounting**

As standard, a telephone mounting panel is fitted to the inner back panel of the kiosk.

Supplied fully assembled, the kiosk can be made available for future dismantling making it possible to install where the fully assembled kiosk cannot fit, through a doorway for example.





## GRP Kiosk



### Optional

Optional extras are internal lighting, carpeting and a translucent roof which allows a natural light source.

A double glazed window unit can also be fitted to the door upon request.

### Specifications

- Body & Door Material: Polyester Resin, Fire resistance - BS476 Part 7 Class 1 surface spread of flame
- Floor Material - Polyester resin
- Acoustic Insulation - 50mm tissue-faced non hygroscopic Rockwool
- Insulation Retainer - Pre-galvanised flattened Experf
- Apparatus plate - 316 Grade stainless steel, powder coated white
- Window - 4mm Clear polycarbonate

### Size

- Dimensions: H2120mm W930mm D930mm
- Weight: Approx. 125Kg

### Colours Available

- Standard colour is Yellow (RAL 1006)
- Can be made in many colours - please enquire for details

